



Ladelänge	Radstand	Überhang	Gesamt-länge	Ladevolumen (m ³) bei Ladehöhe					
				1900	2000	2100	2200	2300	2400
8500	5225	1590	9850	38,2	40,1	42,2	44,2	46,2	48,3
9000	5900	1590	10500	40,4	42,5	44,6	46,8	49,0	51,1
9500	6250	1590	10850	42,7	44,8	47,1	49,4	51,7	54,0
10000	6500	1840	11350	44,9	47,2	49,6	52,0	54,4	56,8
10500	7000	1840	11850	47,1	49,6	52,1	54,6	57,1	59,6
11250	7875	1840	12750	50,5	53,1	55,8	58,5	61,2	63,9

Fahrzeug ist beladen bemaßt

		Oberfläche	Maßstab 1:40	Position	-	Gewicht
		Id.-Nr.:		St		
		-		-		
		Datum	Name			
		Bearb. 07.10.2021	MMETZ			
		Gepr. 07.10.2021	DSCHMIDT			
		Norm				
		SKM34/3 OH - SAnh.				
		8500-11250x2330x...				
		Stahl-Rundmulde Typ 3L				
		626.A16.55-3		Blatt 3		
		626A1655-3_00		a3		
Zust.	Änderungen	Datum	Name	Dateiname	626A1655-3_00	

